

# LIXAS TATU



TRADIÇÃO EM ABRASIVOS

## PRODUCT TECHNICAL SHEET

### Applications

Used for grinding and finishing in a single operation without switching discs. Surface leveling, grinding of weld beads and ends, and grinding of burrs. **Produced with Zirconium Abrasive and Aluminum Oxide.**

### Composition & Technical Data

- **Abrasive:** Zirconium Abrasive and Aluminum Oxide;
- **Diameter:** 4,5" ou 115mm;
- **Hole:** 7/8" ou 22,2mm;
- **RPM MAX:** 13.300 - 80m/s;
- **Available grains:**
  - P40**
  - P60**
  - P80**
  - P120**
- **Package:** 10 discs.
- **Discs with 60 sheets of 18 x 24,5mm**



## STANDARD FLAP DISC

# STANDARD FLAP DISC

## Composition

Cloth, abrasive, adhesive, fiberglass mesh, metal and epoxy glue.  
**Note: Does not contain heavy metals. Non-reactive material.**

## PROFESSIONAL USE FIBERGLASS SUPPORT

- Roughing and finishing;
- Low noise and vibration;
- Fewer disc changes;
- Better finish;
- Good material removal;
- High performance;

## Benefits

## Security

Grinding operations produce sparks, chips and filings, which are extremely important for eye protection. Use the necessary PPE according to the operation: Safety Glasses, Face Shields, Dust Masks, Gloves. The discs must be protected using a protective cover suitable for each piece of equipment. Handle with care, avoiding falls and bumps; any damage should not be reassembled. **Use the disc at an angle of 10 to 25 degrees in relation to the piece. More information can be found in the standard "ABNT NBR 15230 – Abrasive Tools – Use, handling, safety, classification and standardization".**

## Storage

The product must be stored in its original packaging at a temperature between 15° C and 27° C and relative humidity between 35% and 50% and away from floors, windows and damp places.

## Validity

Under the above conditions, the validity is 3 years.

**SAC**

sac@lixastatu.com.br

Indústria e Comércio  
Gotthard Kaesemodel S.A  
CNPJ: 84.685.478/0002-73  
INDÚSTRIA BRASILEIRA  
Av. Brasil, 1728 - Ferraz de  
Vasconcelos (Sp) - Cep: 08529-310

+55 11 4674-6216  
+55 11 98197-3131  
www.lixastatu.com.br  
@lixastatu

EMPRESA  
CERTIFICADA  
ISO 9001



**GK**  
ABRASIVOS